

# ACL800-PB-S

**Touch capacitive push button, stand alone, surface mount, silver**

## Product description

---

ACL800-PB Series is a Request-To-Exit Surface mount Push Button switch, it will work independently (standalone) or can equally be connected via a controller to provide exit from a secured area (Push Button Input). It includes a buzzer and a dual LED. The ACL800-PB Series can work in pulse (3, 5, 10 sec) or latch mode.

## The ACL800 range

---

The ACL800 Series consists of all the required elements to establish a range with a state-of-the-art design. This new range, consisting of readers, stand-alone keypad readers and Request-To-Exit touch sensitive push buttons, provides all you need for a coherent look-and-feel attractive project. Moving forward, this product range will be further developed with biometric readers.



## Details

---

- Indoor/outdoor
- Dust proof and water-resistant (IP65)
- Attractive and timeless design
- Touch Sensitive Technology
- Includes a buzzer
- Dual LED
- Work in pulse (3, 5, 10 sec) or On/Off latched mode
- Surface mount
- Backlight illumination
- Request-To-Exit Touch capacitive push button

# ACL800-PB-S

Touch capacitive push button, stand alone, surface mount, silver

## Technical specifications

---

### System

---

RTE (Request To Exit)	Yes
No. of LEDs	2
Language installation manual	English

---

### Technology

---

Request to Exit	Touch Sensitive
-----------------	-----------------

---

### Interface & connections

---

Connector type	Pigtail
Pigtail length	100 cm
Exit	Relay 1A (NO/C/NC)
Relay Output	On/off Latched or Timed (3, 5 or 10 seconds)

---

### Tamper type

---

Pry-off tamper	No
Opening tamper	Yes

---

### Operation

---

Stand-alone	Yes
Backlighting	Green (Door opened) - Red (Door Closed, Denied, Blocked) - Orange (Idle)

---

Visual and Sound signals Complete button lighting + buzzer

---

### Electrical

---

Power supply type	VDC
Power supply value	5 to 24 VDC 15 to 24 VAC
Current consumption	100 mA at 24 VDC Maximum 65 mA at 24 VDC Typical 65 mA at 12 VDC

---

### Physical

---

Physical dimensions	92 x 51 x 25 mm
Net weight	163 g
Shipping weight	295 g
Colour	Silver
Material	Moulded aluminium
Form factor	Mullion
Mounting type	Surface mount

---

### Environmental

---

Environment	Indoor / Outdoor
Operating temperature	-20 to +50°C
Storage temperature	-20 to +50°C

---

### Regulatory

---

Compliance	CE, RoHS
------------	----------

---



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit [firesecurityproducts.com](http://firesecurityproducts.com) online or contact your sales representative.

Last updated on 17 August 2022 - 16:27