

APS-412

BACKUP POWER SUPPLY

The switching mode power supply designed to power 12 V devices. It is equipped with a dedicated connector for use with SATEL devices. Its design enables it to be easily installed in the SATEL offered enclosure or on the DIN rail.

- EN50131-6 Grade 2 compliant
- high efficiency 12 V DC switching mode power supply, requiring no mains transformer
- 4 A total output current
- short circuit and overload protection
- designed for use with sealed lead-acid batteries
- optionally selected battery charging current
- battery deep discharge protection
- 3 OC outputs for trouble indication
- optical indication of mains, battery and overload status
- audible trouble signal
- dedicated connector for use with new SATEL modules
- designed for mounting on DIN 35 mm rail and in **OPU-3 P**, **OPU-4 P** and **OPU-4 PW** enclosures



TECHNICAL DATA

Environmental class	II
Power supply type	A
Enclosure dimensions	77 x 122 x 59 mm
Operating temperature range	-10...+55 °C
Supply voltage	230 V AC
Weight	306 g
Battery failure voltage threshold (±10%)	11,5 V
Battery cut-off voltage (±10%)	10,5 V
Rated output voltage	12 V DC
Output current	4 A
Battery charging current (switchable)	0,5 A / 1 A
Current-carrying capacity: WS, WB, WP (OC type) outputs	50 mA
Current consumption by power supply circuits	57 mA



The actual appearance of the products may differ from the presented images. Product descriptions are provided in the web service for information purposes only.