



AS367

Sounder-Beacon, Multi Tone, Deep Base

General

The AS367 is a general purpose sounder w/ visual indicator which features a special base containing all wiring connections and allow for easy removal/placement.

Easy and Fast Installation

The AS367 alarm sounder w/ visual indicator allows faster installation and maintenance thanks to an innovative mounting base. Dispensing with the need for locking screws, these sounders use a deep base version of the TimeSaver™ base from the 630 series detectors. Heads are simply locked onto the base with a “twist and click” action, allowing fitting or removal at any time because the base is the only component that needs to be wired. As the cabling requirement is reduced, commissioning time and costs are reduced as well.

Efficient and versatile

The AS367 provide high sound output at a low current, thus reducing power requirements and system cost. The AS367 sounder w/ visual indicator is supplied with a volume control as standard, allowing final audio adjustments to be made during installation.

With a choice of 32 different tones (see tones table in manual), which are switch selectable, the required tone can be selected during installation.

The mechanism for locking the sounder w/ visual indicator to the base, can be activated if required. Once activated, a special tool is required to remove the sounder from the base.

The AS367 sounder w/ visual indicator utilises a full faced translucent sounder case, giving a much larger lens area and a greater spread of light.



Details

- High sound output
- Low current consumption
- 32 Tones user selectable
- Automatic synchronisation
- Volume control
- Anti-Tamper locking mechanism
- Deep mouting base
- Wiring directly to base
- Seperate sounder and visual indicator connections
- EN54-3:2001 (Tones 1,2,3,6,7,13 only)
- Note: The visual indicator of this product does not comply with EN 54-23 and must not be used in fire alarm installations where fire notification beacons are required.

AS367

Sounder-Beacon, Multi Tone, Deep Base

Technical specifications

VID

Flash frequency	1 Hz
	60 flashes/min

Physical

Physical dimensions	100 x 104 mm (Ø x D)
Net weight	250 g

Environmental

Operating temperature	-25 to +70°C
Environment	Indoor, Outdoor
IP rating	IP65

Regulatory

Certification	EN54-3
---------------	--------

Operation

Continuous

Supply voltage

17 - 60 VDC

Current consumption

Sounder (see tone table in manual) 4 - 41mA @ 24 VDC

Visual indicator	5mA @ 24VDC
------------------	-------------

Sound output @ 1 metre

(see tone table in manual) 94 to 106dB(A)

Number of tones

32

Automatic synchronisation

Phased start

Housing

High impact polycarbonate

Ingress protection

IP65

Operating temperature

-25°C to +70°C

Dimensions (Ø x D)

Deep base	100 x 104 mm
-----------	--------------

Weight

250g

Color base

Red

Color lens

Red



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 3 August 2022 - 15:39