

AS505

Outdoor siren with single amber beacon



Details

- Attractive high quality shaped housing
- Double piezo sounder with 114 dB @ 1m sound output
- Vertical or horizontal mounting
- Fully potted electronics
- Strobe flash light
- Selectable comfort LED indication
- Pry-off and opening tamper detection
- Self detection of cable cutting or tampering
- Installer friendly
- Hold-off polarity selection
- Independently hold-off for both beacon and siren
- A choice of cut off time
- Selectable tamper configuration

AS505

Outdoor siren with single amber beacon

Technical specifications

General

Accessory group	Siren
Type	Outdoor siren
Sounder output (dB @ distance)	114 dB at 1 m (typical)
PCB protection	Fully potted
Tamper & pry-off	Yes
Cut-off timer	3 min, 5 min, 10 min, 20 min
Comfort LED	Yes
Sounder	Double piezo
Low voltage detection	Yes
Metal inner cover	Optional

Flash specifications

Flash frequency	50 to 60 flashes/min
-----------------	----------------------

Electrical

Operating voltage	10 to 14.5 VDC
Current consumption	350 mA

Physical

Physical dimensions	212 x 300 x 55 mm
Material	Polycarbonate
Material (housing)	Polycarbonate (3 mm)

Environmental

Operating temperature	-25 to +55 °C
IP rating	IP54

Frequency

	0.5 to 3 kHz
--	--------------



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 8 April 2024 - 13:15