

# ASW366

## Sirene Vermelha de Parede com Alarme Visual EN54, Base Baixo Perfil - Convencional

### General

---

The ASW366 is a RED, general purpose, wall mount, electronic sounder and beacon for fire alarm applications. It features a special base containing all wiring connections allowing for easy placement or removal of the device. With an EN54-23 approved coverage pattern of W-2.4-7.5 for the beacon, each ASW366 may be mounted up to 2.4m high and cover a square room of 7.5 x 7.5m with a single device.

### Easy and Fast Installation

---

The ASx360 series alarm sounder/beacons allow faster installation and maintenance thanks to an innovative mounting base. Dispensing with the need for locking screws these devices use TimeSaver™ bases from the 630 series detector lines. Heads are simply locked onto the base with a “twist and click” action, allowing fitting or removal at any time because the base is the only component that needs to be wired. As the cabling requirement is reduced, commissioning time and costs are naturally reduced as well.

### Efficient and versatile

---

The ASx360 series sounders provide high sound output at a low current, thus reducing power requirements and system cost. They are supplied with a volume control as standard, allowing final audio adjustments to be made during installation. With a choice of 32 different tones (see tones table in manual), which are switch selectable, the required tone can be selected during installation.

The ASx360 series beacons utilise a specially designed lens giving a uniformed light output over the specified coverage area.

The mechanism for locking the device to the base may be activated if required. Once activated, a special tool is required to remove the sounder from the base.



### Details

---

- High sound output with Pulse Alert™ technology
- 32 Tones user selectable
- Automatic synchronisation
- Volume control and adjustable flash rate
- Anti-Tamper locking mechanism
- Shallow mouting base with wiring to the base
- Seperate sounder and beacon and control
- EN54:3 and EN54:23 approved, CPR Certified

# ASW366

## Sirene Vermelha de Parede com Alarme Visual EN54, Base Baixo Perfil - Convencional

### Technical specifications

#### Allgemein

Monitorização de linha Polarised input

#### Elektrische Angaben

Tensão de operação 17 to 60 VDC

Consumo de corrente Sounder: 5.1mA

Beacon: 20mA @ 0.5 Hz

#### Signalgeber

Nível de saída 85 to 97dB(A) @ 1 m (tone dependant)

Tons selecionáveis 32

Sincronização Phased start

Nr. de etapas Automatic

#### Physikalische Angaben

Dimensões físicas 100 x 100 mm (Ø x D)  
Shallow base

Peso líquido 215 g

Cor Vermelho

Material Policarbonato de alto impacto

#### Umweltbedingungen

Temperatura de operação -25 to +70°C

Humidade relativa 5 to 95% noncondensing

Ambiente Interior

Classificação IP IP21

#### Regulatory

Certificação EN54-23, EN54-3

#### Operation

Continuous

#### EN54-23 rating


Light coverage W-2.4-7.5

Mounting position Wall

Mounting height up to 2.4 m

Floor coverage up to 7.5 x 7.5 m

#### EN54-23 Coverage: W-2.4-7.5



Como empresa de inovação, a Carrier Fire & Security reserva o direito de alterar as especificações do produto sem aviso prévio. Para obter informações sobre as especificações mais recentes do produto, visite [pt.firesecurityproducts.com](http://pt.firesecurityproducts.com) online ou contate o departamento comercial.

Last updated on 3 August 2022 - 15:42