



# ATS1181

## Secure Mifare DesFire EV1/EV2 card reader with PIN, output and RTE input in slim design

### Product overview

---

The ATS MIFARE DESFire EV1/EV2 readers connect directly to the control panel or 4 door controller using the ATS databus.

Communication to Advisor Advanced control panels is AES encrypted, providing data to be securely communicated from the card to the processing unit. The readers are configured through locally through keypad and control panel menu or addressed through the ATS1482 addressing card. Select secure cards from the ATS145x secure card series.

The reader offers a Request To Exit input and one open collector output that can be used to control a door relay or door strike.

The ATS Mifare Desfire EV1 readers are designed to transfer card data is a secure and reliable way in various environments. The card data is by default secured by an Interlogix own security key, but can be changed easily in Advisor Advanced control panels to any custom required key.

The readers can optionally be set to read MIFARE CSN numbers instead in unsecure mode.

### Communication

---

The reader communicates over the Advisor databus to Advisor control panels and 4 door controllers. When connected to Advisor Advanced control panels the data between reader and control panel is AES encrypted, securing the data from the card or the PIN code until being processed.

### Design

---

The unique design of the housing guarantees that the reader can be used in the most demanding surroundings having IP67 and IK-09 ratings. Readers can be installed directly on to a metal surface without any insulation.



### Details

---

- Secure ATS Mifare DESFire EV1/EV2 reader with PIN keypad
- Supports Secure Mifare (secure mode) or Mifare 4 or 7 byte CSN/UID (Unsecure mode)
- Use secure ATS145x series cards or customer cards
- Secure communication using AES-128 bit encryption between reader and Advisor Advanced / CDC4 control panel
- Robust molded plastic housing in slim design
- Indoor or outdoor mounting
- ATS bus interface
- Request To Exit input
- Open Collector Output (door open)
- Supported as of Advisor Advanced MR4.2

# ATS1181

## Secure Mifare DesFire EV1/EV2 card reader with PIN, output and RTE input in slim design

### Technical specifications

#### System

|                               |  |
|-------------------------------|--|
| Reading distance              | Secure: max 2 cm<br>Unsecure: max 5 cm |
| Max. reader distance to panel | 1500 m                                 |
| CSN (Card Serial Number)      | Yes                                    |
| Custom data model             | Yes                                    |
| Addressing type               | Card Addressing                        |
| No. of LEDs                   | 3                                      |

#### Technology

|   |  |
|---|--|
| Reader type                             | Smart Card   |
| Reader operating-transmitting frequency | 13.56 MHz  |
| Supported technology 13.56 MHz          | MIFARE Classic (CSN), MIFARE DESFire (CSN), MIFARE DESFire EV1 (Aritech), MIFARE DESFire EV1 (CSN), MIFARE DESFire EV1 (custom data), MIFARE DESFire EV2 (Aritech), Mifare DESFire EV2 (CSN), Mifare DESFire EV2 (custom data) |
| No. of Mifare bytes CSN                 | 4 Byte (non-unique), 4 Byte (S50), 7 Byte (S50), 7 Byte (S70)  |

#### Interface & connections

|                |            |
|----------------|------------|
| Interface      | ATS RS-485 |
| Connector type | Pigtail    |
| Pigtail length | 2 m        |

#### Inputs/outputs

|         |                          |
|---------|--------------------------|
| Inputs  | Request to exit          |
| Outputs | 1 Open Collector (10 mA) |

#### Tamper type

|                |     |
|----------------|-----|
| Pry-off tamper | Yes |
|----------------|-----|

#### Operation

|            |                          |
|------------|--------------------------|
| PIN keypad | Yes                      |
| PIN length | Defined by control panel |

#### Electrical

|                     |  |
|---------------------|--|
| Operating voltage   | 10.8 to 30 VDC                                   |
| Current consumption | 50 mA @ 13.8 VDC normal<br>80 mA @ 13.8 VDC max. |

#### Physical

|                     |                  |
|---------------------|------------------|
| Physical dimensions | 140 x 44 x 20 mm |
| Net weight          | 240 g            |
| Shipping weight     | 275 g            |
| Colour              | Black            |
| Material            | Plastic          |
| Form factor         | Slimline         |
| Mounting Type       | Surface mount    |

#### Environmental

|                       |                  |
|-----------------------|------------------|
| Operating temperature | -40 to +55°C     |
| Storage temperature   | -40 to +55°C     |
| Environment           | Indoor / Outdoor |
| IP rating             | IP67<br>IK-09    |

#### Regulatory

|               |     |
|---------------|-----|
| Compliance    | CE  |
| Certification | VdS |



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit [firesecurityproducts.com](http://firesecurityproducts.com) online or contact your sales representative.

Last updated on 12 August 2022 - 10:05