



ATS Smart Card Reader

ATS1190

ATS Smart card reader with 2.5m cable

The ATS1190 smart card readers connect directly on the RS485 data bus of the control panel or 4-Door Controller and may be configured and addressed via a LCD keypad. Some security options (Site code & 4-byte security code) are only programmable via TITAN and configuration cards. The ATS1190 is supplied standard with a white removable dress cover, which can be interchanged with one of four other colours available (see Ordering Information).

Specifications

Supply voltage	9 - 14 V
Current consumption	25 - 80 mA
Open collector output	1(25 mA max)
"Request to exit" input	Yes
Max. distance from panel	1.5 km
Max. number per panel bus	16
Specified cable	Aritech WCAT 52/54 or equivalent
Data bus monitoring	Continuously monitored for offline condition of all devices on data bus
Addressing	Via keypad, TITAN or config. card
IP rating	IP54
Dimensions (W x H x D)	36 x 110 x 20 mm
Operating temperature	-35 to +66°C
Colour	5 colours
Programmable OC output	pulse from 1 msec to 2.5 secs time from 1 sec to 193 days latch
Connectivity	RS485 data bus device or standard Wiegand for connection on the 4 reader inputs of the ATS1250
Read range (cm)	6 - 8
Optical pry-off tamper sensor	Yes
Epoxy-filled weatherproof construction	Yes
Red & Blue LEDs	Configurable as nightlight, lock status or alarm area status supplied with 2.5 m of cable



- Full epoxy filled weather proof construction
- Standard white snap-on cover (optional red, black, beige, grey)

Ordering Information

ATS1190	ATS Smart Card Reader
ATS1660	ATS1190 snap-on cover, White (10 pieces)
ATS1661	ATS1190 snap-on cover, Red (10 pieces)
ATS1662	ATS1190 snap-on cover, Grey (10 pieces)
ATS1663	ATS1190 snap-on cover, Beige (10 pieces)
ATS1664	ATS1190 snap-on cover, Black (10 pieces)
ATS1471	ATS keyfob
ATS1475	ATS proximity card, packed by 10 pcs.
ATS1476	ATS proximity card, with Magstripe,
ATS1477	ATS fibertag.