

# ATS1253

## Controlador Inteligente para 4 portas - PSU 12VDC, Caixa Metálica

### Data Gathering Panels

---

Data Gathering Panels (DGP) are used to expand the number of alarm inputs on the system and allow inputs and relays to be connected at a location remote from the Advisor MASTER panel. DGPs communicate via poll & reply messages and send alarms to the control panel for processing. The DGPs collect information from detectors, door contacts and other similar devices. There are DGPs available for conventional devices, wireless devices as well as for intelligent addressable devices. This special DGP, also called 4-Door controller, is available for collecting the information for four doors.

### Product Overview

---

The ATS1253 4-Door controller is a versatile access control panel to extend the Advisor MASTER system with advanced access control functions. Real time alarm and access control on 4 doors, with power supply and housing. A total of twelve 4-Door controllers can be connected to an Advisor Master panel. To program the controllers a user interface with liquid crystal display must be included in the system.

### Extensive programming features

---

Can be used to program a sequence of unique events for a desired outcome (macro logic). For example when a user badges a card or selects a floor, lights in the area can be programmed to turn on or a macro can activate a light on a map at a security desk to indicate a floor has been accessed.

### Connectivity

---

A total of twelve 4-Door controllers can be connected to an Advisor Master panel. To program the controllers a user interface with liquid crystal display must be included in the system.

### Communications

---

The controllers can be mounted up to 1.5 km from the Advisor Master panel, which will continuously check if the controller is still on line. The 4-door controller and the 4-lift controller can operate off-line with no degradation in performances, should communication with the Advisor Master panel fail.

### Users

---

The 4-door controller and the 4-lift controller are using the user information from the Advisor Master panel. The number of card users is 11466. 1000 users can be programmed with a PIN code and with a name.

### Access control procedures

---

Access control procedures like swiping a card or entering a PIN, can be programmed to function only within particular blocks of time or outside those times. For example, during a period deemed as a high



### Details

---

- Real time alarm & access control on 4 doors
- Full mirror database for offline condition
- Max 12 4-door controllers and 48 intelligent doors/panel
- Global anti-passback
- Region control
- User counter, interlocking, card + PIN
- 8 alarm inputs on board
- Local RS485 bus for up to 16 readers
- Wide range of third party readers supported
- 4 relays on board for lock strikes
- 52 programmable outputs
- 12V Lock power, 4A power supply

security risk, granting access may require a PIN and card to be presented at reader. At another time of low security risk, access to the same area may be gained with only the presentation of a card.

## **Door groups**

---

The 4-door controller is also using the door groups from the Advisor Master panel. Standard there are 128 door groups available.

## **Timezones and holidays**

---

The controllers can use one or more of the 24 free programmable time zones and 24 holiday slots.

## **Inputs**

---

The ATS1253 has eight 4-state monitored inputs on board. On the 4-door controller, by default 8 inputs are assigned to Request to Exit buttons and door contacts, but they can also be re-programmed as regular inputs.

## **Readers**

---

The ATS 1253 supports many reader formats including magnetic swipe, PIN code, proximity and Wiegand.

# ATS1253

## Controlador Inteligente para 4 portas - PSU 12VDC, Caixa Metálica

### Technical specifications

<b>Geral</b>		<b>Addressing</b>	
Tipo de expansor	Controlador de Portas	Individually addressed via DIP switches	
Linha de produto	Advisor Advanced, ATS Master	<b>Users</b>	
Tipo de ligação	Databus connection	11466 cardholders (expandable to 65535 with IUM)	
Distância máx. do painel	1.5 km	<b>PIN codes</b>	
Cabo especificado	Aritech WCAT 52/54 or equivalent	1000 dependant on panel memory options	
<b>Entradas</b>		<b>Door groups</b>	
Total	32	128	
Expansíveis	24	<b>Time zones / Holidays</b>	
<b>Saídas</b>		24 / 24	
Incorporadas	8	<b>Zones</b>	
Relés	4 on-board (expandable to 52 with relay cards)	8 (free programmable inputs)	
<b>Sistema</b>		<b>Relays</b>	
Utilizadores	mais de 1000	4 on-board (expandable to 52 with relay cards)	
Códigos PIN	1000 dependant on panel memory options	<b>Operating temperature</b>	
Grupos de portas	128	0 to +50°C	
Zonas Horárias/ feriados	24/24	<b>Mains transformer</b>	
Endereçamento	DIP Switches	230 V 50 Hz / 129 VA	
<b>Backup</b>		<b>Housing dimensions (W x H x D)</b>	
Teste dinâmico de bateria	Yes	445 x 315 x 90 mm	
<b>Elétrica</b>			
Tensão de operação	13.8 V		
Tipo de fonte de alimentação	VDC		
Consumo de corrente	4000 mA		
Fonte de alimentação integrada	Sim		
<b>Físico</b>			
Dimensões físicas	445 x 315 x 90 mm		
<b>Ambiental</b>			
Temperatura de operação	0 to 50 °C		
<b>Power supply</b>			
	13.8 VDC / 4000 mA		
<b>Battery test</b>			
	Dynamic battery testing		
<b>Max. distance from panel</b>			
	1.5 km		
<b>Specified cable</b>			
	Aritech WCAT 52/54 or equivalent		
<b>Data bus monitoring</b>			
	Continuous monitoring for off-line conditions of all devices on bus		

As a company of innovation, UTC Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit UTC Fire & Security online or contact your sales representative.

25 February 2019 - 17:56



**United  
Technologies**

Climate | Controls | Security