

ATS1870 ATS card learn reader (USB) for Hitag2 and Mifare CSN

ATS card learn reader (USB)

The versatile reader combines support for Hitag2 and Mifare CSN cards in combination with ATS8600 Advisor Management or the ATS85xx Downloaders. The USB reader provides for an easy method to add cards into the security system, as well as support the simultaneous use of Hitag2 and Mifare CSN.



Details

- Support card learning for ATS8600 and ATS85xx Downloaders
- Supports Mifare CSN in 4 and 7 byte with adjustment to 48 bit option
- Supports Hitag2 UID cards
- Four ID badge configurations (3 are pre-set, all four are user definable)
- Select options through small application

ATS1870 ATS card learn reader (USB) for Hitag2 and Mifare CSN

Technical specifications

System	
CSN (Card Serial	Yes
Number)	
Custom data model	No
Supported card types	HiTag2, MIFARE® Classic UID
Technology	
Reader type	Multi-frequency
Reader operating- transmitting frequency	125 KHz, 13.56 MHz
Supported technology 13.56 MHz	MIFARE Classic (CSN)
Supported technology 125 kHz	HiTag 2
No. of Mifare bytes CSN	4 Bytes (non-unique), 4 Bytes (S50), 7 Bytes (S50), 7 Bytes (S70)
Read / write	No
Interface & connec	tions
Interface	USB
Connector type	USB
Electrical	
Current consumption	70mA
Physical	
Physical dimensions	9cm x 5.2cm x 1.6cm
Net weight	113gr
Colour	Black
Environmental	
Environment	Indoor
Regulatory	
Compliancy	CE, FCC, REACH, RoHS



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.