

BS130N

Battery 12 V, 12 Ah

Product overview

Sealed Lead Acid battery 12 V / 12 Ah with Fast-on 6.35 mm terminal type.



Details

- Maintenance free
- Lead-Calcium grid for extended life
- Wide operating temperature range
- Usable and rechargeable in any position
- Low self-discharge and long service life
- Leakproof construction
- High discharge rate capacity

BS130N

Battery 12 V, 12 Ah

Technical specifications

General

Product type	Sealed lead acid battery
--------------	--------------------------

Electrical Characteristics

Nominal voltage	12 V
Nominal capacity	12 Ah
Internal approx. resistance	13 mOhm

Charge / discharge

Max. charge voltage	13.8 VDC at +20°C
Max. charge current	3.6 A
Max. discharge current	60 A

Temperature

Charging temperature	0 to +40°C
Discharging temperature	-15 to +50°C

Physical

Physical dimensions	151 x 98 x 98 mm
Net weight	4.27 kg
Shipping weight	4.27 kg
Material	ABS
Terminal type	Fast-on 6.35 mm

Environmental

Fire retardant	No
Operating temperature	0 to +40°C
Storage temperature	-15 to +50°C

Standards & regulations

Compliance	CE, RoHS 2, WEEE
Certification	VdS



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 16 May 2022 - 13:56