



## Product Data Sheet

# DC115

Surface - overhead - door mount contact - biased

### Industrial Contact

The DC115/DC118 are designed to be installed in commercial and industrial environments where a rugged sealed unit is required. It is ideal for metal doors, overhead doors, fences and gates. Each model features a high strength extruded aluminium housing and is completely encapsulated in an exclusive polyurethane potting compound.

### Comprehensive Range

The range features wide gap distances and several models to meet any application need. Armoured cable is available.



### Standard Features

- Mounting brackets available for gates, garage doors, freezers
- Rugged construction for long life
- Convenient surface mounting
- 2 m armoured cable
- Tamper loop provided
- DC115 is polarity-sensitive with reference to magnet direction

# DC115

Surface - overhead - door mount contact - biased

## Specifications

Operating gap	9 mm (min.); 62 mm (max.)
Connections (armoured cable)	5 wires, 2 m
Contact type	CO
Dimensions (W x H x D)	
Magnet	76 x 12 x 25 mm
Contact	76 x 12 x 25 mm
Material	Anodised aluminium finish

## Ordering Information

Part No.	Description
DC115	Surface - overhead - door mount contact - biased
DC118	Surface - overhead - door mount contact - wide gap
DC111	Surface - overhead - door mount contact - triple biased
DC1912	L Bracket for DC110, DC115, DC118

