

DMN700R100-KITR

Conventional MCP, Surface Mount, Red, 100 Ω & Free Contact, Resettable

General

The DMN700R100-KITR is a red manual call point for surface mount applications. It has an internal 100 ohm series resistor and free contact. It is supplied complete with a resettable element, test key and surface mount box.

Installation

Installation time and ultimately cost, are of paramount importance. The MCP range directly reflects this need by providing a unique 'plug and play' concept designed specifically to reduce installation time. All new MCP products utilise a special terminal block, where all initial installation cabling is terminated. This terminal block is then simply connected to the back of the MCP. Simple, but effective, with no re-termination required and no time wasted.

Options and approvals

Through new standards and legislation, both break glass and re-settable operating elements may now be used. To provide the greatest 'flex-ability', the new MCP range can be configured as either a break glass or re-settable unit by simply changing from one element to another. No other additional parts or alternative products are required. Full compliance with the latest standards is essential and the new MCP indoor call point range is fully approved to the latest EN54-11 standard.



Details

- Enhanced aesthetics
- Easy to install (plug and play)
- Surface mount options
- Protection hinged cover with Anti-Tamper facility
- Backward compatible
- Key test facility
- May be used with glass or resettable element
- Easy to replace glass
- High quality micro switch
- Fully approved to the latest standards

DMN700R100-KITR

Conventional MCP, Surface Mount, Red, 100 Ω & Free Contact, Resettable

Technische specificaties

General

Status indication	Alarm Flag
Compatibility	Conventional alarm systems

Electrical

Cable specification	0.5 to 2.5 mm ² (cable termination)
No. of cable cores	2

Detection

Monitoring	Off, On
Installation height	Determined by local regulation

Output

Output quantity	2
Output type and rating	2 A @ 30 VDC (resistive load), 100 Ω in series

Physical

Physical dimensions	89 x 88 x 58 mm (W x H x D)
Net weight	110 g
Colour	Red
Mounting type	Back box
Cable entries	1
Material (body)	PC/ABS
Functional marking	House on Fire

Environmental

Vandal proof	No
Operating temperature	-10 to +55°C
Storage temperature	-10 to +55°C
Relative humidity	0 to 95% noncondensing
Environment	Indoor
IP rating	IP24D

Regulatory

Compliance	CE, REACH, RoHS 2, WEEE
Certification	EN54-11



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 25 May 2022 - 10:53