

The DM2010 is a RED surface mount, addressable 2000 series manual call point with a high strength plastic housing suitable for indoor applications. The LED indicator provides visual confirmation of alarm initiation. The test key (included with each unit) facilitates functional testing of the call point. The manual call point is delivered complete with glass, but a resettable element can be installed as an option at any time.

Specifications

Power supply	
Operating voltage	17-28 VDC
Voltage modulation	4-9 V
Current consumption	
Quiescent	< 250 microA
Alarm	< 2.5 mA
Environmental	
Operating temperature	-10°C to +55°C
Storage temperature	-25°C to +70°C
Operating humidity (noncondensing)	10-95 %
Ingress Protection	IP24D
Physical	
Cable specification	0.8 to 2.5 mm ²
Dimensions (L x W x H)	89 x 93 x 27.5 mm
Weight	188 g



- Addressable manual call point
- LED alarm indicator
- Tamper resistant break glass design
- Easy to test with auto reset
- Fast response
- IP67 waterproof model available

Ordering Information

DM2010	2000 Series Addressable Manual Call Point (RED)
DMN782	Hinged transparent MCP protection cover
DM790	Flush mount cradle with connectors
DM795	Flush mount cradle, connectors & forkgrrips
DMN798	Breakable Seal for Manual Call Points
DMN800	Resettable Element for Manual Call Point