



DP2061N

2000 Series Addressable Optical Detector, Dual LED, Remote Output

General

The DP2061N is a 2000 series protocol, addressable optical detector. It is equipped with a field-exchangeable optical block and is fully CPD certified. This optical detector combines a low profile design with dual alarm LEDs for 360° alarm visibility, and features a remote indicator output as standard.

User Friendly

Every detector is equipped with an internal self-test feature. This test may be activated from the fire panel and allows the detector to perform a self-test for which the result is reported to the panel.

All detectors are individually identified by setting an address through 2 rotary switches. The address is straight numerical and does not require binary or hexadecimal conversions and therefore significantly reduces the risk of incorrect addressing.

Maintenance Friendly

The DP2061N features a disposable optical chamber. This allows the detector to be easily serviced without the need for specialised equipment in the field and without operating through an exchange pool of any kind. A self-test feature as well as drift compensation and contamination warning is provided when used with compatible Aritech fire panels.

All 2000 series detectors are compatible with a standard base, which makes them easily interchangeable.

State of the Art Communication

An enhanced protocol ensures the overall integrity and error-free operation of the system, without compromising speed. The 2000 series protocol provides features such as CRC error checking and multiple bus cycle codes to enable advanced features of the panel to detector communication.

Extended Applications

A comprehensive 2000 series range of detectors and accessories complement the DP2061N detector. Apart from a complete detector line as well as a full line of manual call points, accessories such as isolators, sounder circuit controllers, zone monitor units and a variety of I/O modules are also available.



Details

- Remote signalling capabilities
- Field exchangeable optical chamber
- Easy numeric addressing (1-128)
- Enhanced communication protocol
- Full diagnostic self testing
- Full range of detectors available
- Full range of I/O units and accessories
- Optional isolator base
- EN54:7 approved and CPR certified

DP2061N

2000 Series Addressable Optical Detector, Dual LED, Remote Output

Technical specifications

General

Status indication	Dual red LED
Compatibility	Aritech 2000 systems
Alarm levels	5
Connectivity	2000 Series bases
Addressing method	Rotary switch

Electrical

Power supply type	Loop powered
Operating voltage	17 to 28 VDC
Current consumption	350 μ A (quiescent at 24 VDC) 4 mA (alarm at 24 VDC)

Detection

Detection principle	Optical light scatter
Monitoring	Alarm threshold, Contamination level
Sensitivity	Configurable
Coverage area	< 80 m ²

Output

Output quantity	1
Output type and rating	Remote indicator
Programmable	No
Remote alarm output	4 mA

Physical

Physical dimensions	100 x 50 mm (\varnothing x H)
Net weight	115 g
Colour	Cloud white (RAL 9001)
Mounting type	Base mount
Material (body)	Plastic

Environmental

Vandal proof	No
Operating temperature	-10 to +60°C
Storage temperature	-10 to +70°C
Application temperature (typical)	+25°C
Relative humidity	10 to 95% noncondensing
Environment	Indoor
IP rating	IP43

Regulatory

Compliance	CE, REACH, RoHS 2, WEEE
Certification	CPR
Standards	EN54-7



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 25 May 2022 - 13:35