#### **Product data sheet**



## FE371-N

### Magnetic lock 5400 N, Mega-LED and Relay

#### Mega-LED

This electromagnet is part of the new series of magnetic locks equipped with a "Mega-LED" allowing to see the LED status from a much further distance.

### Security, quality and design

Security, safety and design using high quality materials, ensuring maximum strength without any residual magnetism or corrosion and proven holding force.



#### **Details**

- Strong design with high-end finish
- Corrosion proof: salt spray test (ISO 9227, ASTM B 117-90) at 35% for 96 hours
- No residual magnetism
- Built-in MOV surge protection
- L bracket and Z + L bracket set available

# FE371-N

## Magnetic lock 5400 N, Mega-LED and Relay

## **Technical specifications**

General	
Product type	Magnetic lock
Holding force	
Holding force kgf (Kilogram force)	540
Holding force N (Newtor	n)5400
Monitoring & status	
Monitored	Yes
LED indicator	Yes
Door status switch	No
Electrical	
Operating voltage	12/24 V
Current consumption	500/250 mA
Physical	
Physical dimensions	268 x 73 x 40 mm
Net weight	~ 4 kg
Colour	Aluminium
Environmental	
Operating temperature	-40° to +60°C
Main features	
Mounting	Surface
Locking monitoring	Large L shaped LED for long distance status + Relay
Door position monitoring	g No
Corrosion Proof	Salt spray test. ISO 9227, ASTM B-117 90
Residual magnetism	Guaranteed no residual magnetism
Built-in MOV Surge Protection	Yes

As a company of innovation, UTC Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit UTC Fire & Security online or contact your sales representative.

