



FIRE BEAM

Reflective Optical Beam Smoke Detector



FIRE BEAM is the optimal solution to protect large areas with ceiling height greater than 4 meters. A motorized beam head will self-align itself to the centre of the reflector when commissioning and will automatically keep alignment when building movement occurs which will prevent unwanted false alarms.

Additionally, the ground level controller facilitates any change or adjustment. Its low current consumption enables seamless integration with addressable systems via an Input or ZMU modules. Another relevant feature is related with its environmental protection that makes FIRE BEAM a suitable solution for harsh industrial applications, in situations where condensation may occur, filters with special coating widens the scope of usage.

| TECHNICAL SPECIFICATIONS | |
|---------------------------------|--|
| SUPPLY VOLTAGE / SUPPLY CURRENT | 12 to 30V DC / 3.5 mA (quiescent; alarm; fault) 17mA in fast commissioning |
| NORMAL | Green LEDs Flashing - Controller Message |
| FAULT | Yellow LEDs Flashing - Change over relay (2A@30VDC)/ Controller Message |
| ALARM | Red LEDs Flashing - Change over relay (2A@30VDC)/ Controller Message |
| TEMPERATURE / HUMIDITY | -10°C to +55°C / 10 to 95% RH Non-condensing |
| IP RATING | IP65 when suitably mounted and terminated |
| BEAM HEAD | 180 (H) x 155 (W) x 137 (D) mm / Weight 1.1 Kg |
| CONTROLLER | 185 (H) x 120 (W) x 62 (D) mm / Weight 0.55 Kg |
| 70KIT140 MID-RANGE REFLECTOR | 293 (H) x 293 (W) x 5 (D) mm / Weight 0.8 Kg |
| 140KIT160 LONG RANGE REFLECTOR | 394 (H) x 394 (W) x 5 (D) mm / Weight 1.8 Kg |
| ADAPTER | 270 (H) x 250 (W) x 5 (D) mm / Weight 0.6 Kg (mounts the Beam Head |
| | onto unistrut) |

| ORDER CODE | |
|--------------------|---|
| FIRE BEAM | BASIC FIRE BEAM INCL. CONTROLLER + 1 REFLECTOR COVERS DISTANCE OF 7-70 METERS |
| 70KIT140 | MID RANGE EXTENSION KIT 70-140 M |
| 140KIT160 | LONG RANGE EXTENSION KIT 140-160 M |
| ADAPTER | HEAD INTERFACE ADAPTER TO MOUNT TO UNISTRUT |
| ANTI-FOG FIRE BEAM | ANTI FOG FIRE BEAM |
| 70KIT140-AF | ANTI FOG MID RANGE EXTENSION KIT 70-140 M |
| 80KIT100-AF | ANTI FOG LONG RANGE EXTENSION KIT 140-160M |
| WINDOW-AF | ANTI FOG WINDOW |
| REF-AF | SINGLE ANTI FOG REFLECTOR |
| FOGKIT | ANTI FOG WINDOW FOR HEAD AND SINGLE ANTI FOG REFLECTOR |
| | |



Sitio dos Barrabés, Armazém Nave Y, Caixa Postal 908-Z 8150-016 São Brás de Alportel. PORTUGAL

