



# GFE-MCPE-C

## CONVENTIONAL MANUAL CALL POINT



The GFE-MCPE-C is a Conventional Manual Call Point, designed and manufactured to comply with EN54-11, compatible with all GFE Conventional Control panels. A bi-colour LED flashes Green when the unit is connected to a control panel and is illuminated Red when in Alarm.

The unit is supplied complete with a hinged flap which protects the trigger element from accidental activation and reduces malicious activations as two actions are required in order to activate the device. This unit can be both surface and flush mounted and it can be easily reset using the supplied key after activation.

### TECHNICAL SPECIFICATIONS

OPERATION VOLTAGE	25 (+5; -15) [V DC]
CURRENT - QUIESCENT	200 $\mu$ A
CURRENT - ALARM	50 mA @ 24V DC nominal - Alarm Resistance 470 Ohms max.
OPERATION TEMPERATURE	-10°C to +55°C
STORAGE TEMPERATURE	-30°C to +60°C
PROTECTION	IP24D - Type A - Indoor Use
CABLE SIZE	0.5-1.5 mm <sup>2</sup>
MAX. HUMIDITY	95% RH Non-Condensing @ 40°C
COLOUR	Red
CASE MATERIAL	ABS & Clear/ PC - Flame Retardant 94 V0
DIMENSIONS - SURFACE MOUNTED	92.6 (H) x 92.6 (W) x 60.1 (D) mm
DIMENSIONS - FLUSH MOUNTED	92.6 (H) x 92.6 (W) x 27.8 (D) mm
WEIGHT	152 g includes back box and fixings

*For EN54-13 compliance, please check the control panel manual specifications.*

### ORDER CODE

GFE-MCPE-C	CONVENTIONAL MANUAL CALL POINT	1328-CPR-0377
------------	--------------------------------	---------------