



GS620N

Stand-alone shock sensor

Stand-Alone Shock Sensor

The GS620N shock sensor offers a versatile solution for detection of forced entry through windows or doors. It can be mounted throughout a 360 degrees axis, vertically and horizontally, by ensuring that the brand logo is readable from left to right.

The GS620N is a latching and LED indicating stand-alone shock sensor which includes adjustable gross attack and pulse count sensitivity. It also features first-to-alarm and second-to-alarm LED indication and provides a selectable walk-test facility.

Superior Detection

Its unique design enables the shock sensor to discriminate between a real break-in attempt and everyday background noise by measuring the shock frequency caused by the displacement in the protected structure.

The sensor is designed to activate (contact will open) when an acceleration greater than 1G is detected. This could be caused, for example by a strong blow, a high speed drill or sawing because the frequencies of these shocks fall within the sensors range of detection.

Adjustable Sensitivity

The analysing capability has two separate detection criteria: gross attack and pulse count. The gross attack threshold is designed to react to a single blow, while pulse count alarms when a pre-selected number of smaller shocks, occurring within a 30 second timing interval is reached. Both detection levels can be adjusted so that the installation can be fine tuned to the environment and fully tested using the walk test facility. This digital signal processing is designed to eliminate false alarms and assure reliable detection of all types of attacks.



Standard Features

- Reliable 24 hour loop perimeter protection
- Superior technology provides excellent detection and false alarm immunity
- Suitable for all types of solid structures
- Versatile mounting through 360° axis
- 24 carat gold plated internal mechanics for optimum performance & long life
- Integrated analyser
- Adjustable sensitivity for fine tuning installations

GS620N

Stand-alone shock sensor

Specifications

Detection range	Up to 6 m
LED indication	Yes
Power supply	8 to 15 VDC
Current consumption	
Quiescent	8 mA
Alarm	2.5 mA (LED off)
Operating temperature	-20 to +50°C
Alarm contact rating	0.1 A - 28 VDC
Tamper	28 VDC - 100 mA
Dimensions (W x H x D)	93 x 30 x 25 mm
Colour	White

Ordering Information

Part No.	Description
GS620N	Stand-alone shock sensor
GS620BN	Stand-alone shock sensor, brown
GS625	Stand-alone shock sensor
GS620A	Stand-alone shock sensor, NFa2P
GS620P5N	Stand-alone shock sensor, 5-pack
GS620P5BN	Stand-alone shock sensor, brown, 5-pack

