#### **HD PRO SERIES**

Series dedicated to the installer who's looking for a high-level camera making the difference in terms of image quality.



## **I2-380A-28**

# 20M IR 8MP PRO HD ANALOG FIXED LENS BULLET CAMERA

This 4K bullet camera presents a stunning 8-megapixel image, equipped with a 2.8mm fixed lens, it is designed for short distance surveillance systems (up to 20m) for both indoor and outdoor scenarios. Featuring 4in1 technology selectable by a protected DIPswitch the camera is ideal for Plug & Play over existing analog infrastructure.

























#### **MAIN FEATURES**

- 8MP
- Pro Series
- 3840x2160 Resolution
- Wide field of view 95°
- 3D-DNR
- 4 in 1 (DIP Switch AHD/TVI/CVI/CVBS + PAL/NTSC)
- IP67
- COC support





# **I2-380A-28**





| SPECIFICATIONS         |  |
|------------------------|--|
| Image Sensor           | 1/2.5" 8MP Sensor  |
| Image Format           | 8MP/4MP - 16:9, 5MP - 4:3  |
| Effective Pixels       | 3864x2202  |
| Scanning System        | Progressive  |
| Resolution             | 8MP: 3840x2160 AHD/TVI/CVI<br>5MP: 2592x1944 AHD/TVI<br>4MP: 2560x1440 AHD/TVI/CVI<br>CVBS: 700TVL |
| FPS                    | 8MP @ 12/15FPS, 5MP @ 20FPS, 4MP @ 25/30FPS, CVBS @ 25/30FPS                                       |
| Min. Illumination      | Color: 0.01lux @F1.2, AGC ON<br>B/W:0lux with IR"  |
| D&N                    | True Day&Night-ICR   |
| IR LED                 | 1 LED Array (20m)  |
| OSD Menu               | Available via CoC Only   |
| CoC Support            | Yes  |
| Day & Night Mode       | Ext/Auto/Day/Night   |
| Backlight Compensation | BLC  |
| S/N Ratio              | ≥52dB(AGC OFF)   |
| White Balance          | Auto   |
| Noise Reduction        | 3D-DNR   |
| Video Output           | 8MP / 5MP / 4MP (Selected by OSD Menu) AHD/TVI/CVI/CVBS + PAL/NTSC (Selected by DIP Switch)        |
| Privacy Mask           | No   |
| D-Effect               | No   |
| WDR                    | No   |
| Lens (Field Of View)   | 2.8mm Fixed (95°)  |
| Power                  | DC12V/340mA  |
| Operation Temperature  | -30° ~ 50°, 10% ~ 90% humidity   |
| Protection Rate        | IP67   |
| Dimensions             | 172.2*73.4*74.5mm  |
| Net Weight             | 475g   |
| Junction Box           | PR-JB12IP66 - PR-JB12IP64  |





### DIMENSIONS







### **ACCESSORIES**



PR-JB12IP66 Small Water-proof Junction Box



PR-JB12IP64 Small Junction Box