

Declaration of performance

№ 021/2015

According to Construction Products Regulation EU № 305/2011

1. Unique identification code of the product-type:

SensoIRIS M140

2. Type Number:

SensoIRIS M140

Description:

Intelligent analogue addressable fire alarm heat and optical smoke detector

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer

Fire detection and fire alarm systems installed in and around buildings

4. Manufacturer

Teletek Electronics JSC 14A Srebarna Str. 1407 Sofia, Bulgaria

5. Trading Company

Teletek Electronics JSC 14A Srebarna Str. 1407 Sofia, Bulgaria

6. System of assessment

System 1

7. Notified Body

EVPU a.s. 19 Trencianska Str. 018 51 Nova Dubnica, Slovakia

Notified Body Number

1293

Performed the prescribed tests and evaluation of factory production control according to system 1 and issued the following certificate

EC Certificate Number

1293- CPR-0450

8. No European Technical Assessment has been issued for this product.



9. Declared performance

Essential characteristics	Performance	Harmonized technical specification EN 54-5:2000/A1:2002
Nominal activation conditions / sensitivity,	Pass	4.2, 4.3, 5.2-5.6, 5.8, 6.1, 6.2
response delay (response time)		
and performance under fire conditions		
Operational reliability	Pass	4.4-4.11
Tolerance to supply voltage	Pass	5.7
Durability of operational reliability,	Pass	5.9, 5.10
Temperature resistance		
Durability of operational reliability,	Pass	5.14-5.17
Vibration resistance		
Durability of operational reliability,	Pass	5.11, 5.12
Humidity resistance		
Durability of operational reliability,	Pass	5.13
Corrosion resistance		
Durability of operational reliability,	Pass	5.18
Electrical stability		

Essential characteristics	Performance	Harmonized technical specification EN 54-7:2000/A1:2002 EN 54-7:2000/A2:2006
Nominal activation conditions/Sensitivity,	Pass	4.8, 5.2, 5.3, 5.4, 5.6, 5.7, 5.18
Response delay (response time) and		
Performance under fire conditions		
Operational reliability	Pass	4.2 to 4.7, 4.9 to 4.11
Tolerance to supply voltage	Pass	5.5
Durability of operational reliability and	Pass	5.8, 5.9
response delay; temperature resistance		
Durability of operational reliability;	Pass	5.13 to 5.16
vibration resistance		
Durability of operational reliability;	Pass	5.10, 5.11
humidity resistance		
Durability of operational reliability;	Pass	5.12
corrosion resistance		
Durability of operational reliability;	Pass	5.17
electrical stability		



10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

1407 Sofia,14A, Srebarna Str.14.11.2019

Yuliy Iliev

Quality Manage

CO O U S SOFIA