

Declaration of performance

No 026/2020

According to Construction Products Regulation EU № 305/2011

1. Unique identification code of the product-type:

SensoIRIS MOUT, SensoIRIS MOUT IP55

2. Type Number:

SensoIRIS MOUT, SensoIRIS MOUT IP55

Description: Intelligent analogue addressable fire alarm monitored

output module for conventional sounders with built-in

isolator module

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer

Fire detection and fire alarm systems installed in and around buildings

4. Manufacturer

Teletek Electronics JSC 14A Srebarna Str. 1407 Sofia, Bulgaria

5. Trading Company

Teletek Electronics JSC 14A Srebarna Str. 1407 Sofia, Bulgaria

6. System of assessment

System 1

7. Notified Body

EVPU a.s. 19 Trencianska Str. 018 51 Nova Dubnica, Slovakia

Notified Body Number

1293

Performed the prescribed tests and evaluation of factory production control according to system 4 and issued the following certificate

EC Certificate Number

1293- CPR-0472 Rev.1

8. No European Technical Assessment has been issued for this product.



9. Declared performance

Essential characteristics	Performance	Harmonized technical specification EN 54-18:2005 EN 54-18:2005/AC:2007
Response delay (response time)	Pass	5.2
Operational reliability	Pass	5.1.4
Performance under fire conditions	Pass	5.1.4
Durability of operational reliability: temperature resistance	Pass	5.3, 5.4
Durability of operational reliability; vibration resistance	Pass	5.8 to 5.11
Durability of operational reliability; humidity resistance	Pass	5.5, 5.6
Durability of operational reliability; corrosion resistance	Pass	5.7
Durability of operational reliability; electrical stability	Pass	5.2, 5.12

Essential characteristics	Performance	Harmonized technical specification EN 54-17:2005 EN 54-17:2005/AC:2007
Performance under fire conditions	Pass	5.2
Operational reliability	Pass	4
Durability of operational reliability	Pass	5.4, 5.5
andresponse delay:		
temperature resistance		
Durability of operational reliability:	Pass	5.6, 5.7
humidity resistance		
Durability of operational reliability:shock	Pass	5.9 to 5.12
and vibration		
resistance		
Durability of operational reliability:	Pass	5.8
corrosion resistance		
Durability of operational reliability:	Pass	5.3, 5.13
electrical stability		

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.



Signed for and on behalf of the manufacturer by:

1407 Sofia,14A, Srebarna Str.11.11.2020

Yuliy Iliev

Quality Manager