

IRIS Printer

- Thermal printer in a metal box
- Suitable for modular structure
- Self test and status indication



DESCRIPTION:

The IRIS Printer is a heat printer specially designed for connection to IRIS PRO, iRIS8 and iRIS8 Big Box addressable fire alarm panels. The printer is suitable for building of modular structures with IRIS PRO, iRIS8, iRIS8 Big Box and IRIS PS72 – back-up power supply unit.

IRIS Printer is used for printing of events list and is equipped with independent own power supply.

FEATURES

- Thermal printer in a metal box
- Suitable for modular structure
- Self test and status indication
- Printing method – direct thermal
- Print density: 8 dots/mm, 576 dots/line
- Print speed: max 170mm/sec
- Two type of fonts supported: 12x24 dots and 9x17 dots

TECHNICAL SPECIFICATIONS

- Power Supply.....100-240VAC, 3A
- Serial interface.....RS-232C to IRIS PRO
- Paper width.....80mm, valid print width 72mm
- Print speed max..... 170mm/sec
- Operating temperature.....-10°C to +50°C
- Color.....Grey
- Dimensions.....430x330x117mm

COMPATIBLE PRODUCT RANGE

- IRIS PRO, iRIS8, iRIS8 Big Box addressable fire alarm panels
- IRIS PRO FLM kit

Last update: 04.2021