

# NS4702-24P-4X-V3

## Enterprise-class 24-port Gigabit backbone network switch with PoE+, 4-10G SFP+ uplinks

### Overview

The NS4702-24P-4X-V3 Gigabit IEEE 802.3at PoE+ managed switch provides IPv6/IPv4 dual stack management and built-in L2/L4 Gigabit switching engine along with 24 10/100/1000BASE-T ports featuring 32-watt 802.3at PoE+ and 4 additional 10GBASE-X SFP+ fiber ports. With a total power budget of up to 370 watt for different kind of PoE applications, the NS4702-24P-4X-V3 provides a quick, safe and cost-effective 802.3at PoE+ network solution for small businesses and enterprises.

### Flexibility and Long-distance Extension solution

The NS4702-24P-4X-V3 is a powerful networking device that offers four 10G SFP+ slots capable of supporting three different speeds. These slots can operate at 10GBASE-SR/LR or 1G/2.5GBASE-SX/LX backwards, providing administrators with flexibility in choosing the most suitable SFP/SFP+ transceiver based on the required transmission distance and speed.

### Intelligent Powered Device alive check

The NS4702-24P-4X-V3 supports PD Alive Check which can be configured to monitor connected PD (Powered Device) status in real time via ping action. Once the powered device stops working and responding, the NS4702-24P-4X-V3 will reset the PoE port power and try to bring the PD back to work.

### Extending Ethernet data transmission distance and PoE+ power

In the Extend operation mode, the NS4702-24P-4X-V3 operates on a per-port basis at 10Mbps duplex operation but can support PoE power output over a distance of up to 250 meters overcoming the 100m limit on Ethernet UTP cable.

### PoE schedule for Energy Saving

The PoE schedule function allows you to enable or disable PoE power for each PoE port during specified time intervals. This powerful function offers an easy help to save power and money by for example disabling power for devices during non-business hours.

### Powerful security

The NS4702-24P-4X-V3 offers comprehensive IPv4/IPv6 Layer 2 to Layer 4 Access Control List (ACL) for enforcing security to the edge. It can be used to restrict network access by denying packets based on source and destination IP address, TCP/UDP ports or defined typical network applications. With the protected port function, communication between edge ports can be prevented to guarantee user privacy. Furthermore, Port security function allows to limit the number of network devices on a given port.



### Details

- 24-ports Gigabit Ethernet RJ-45 with PoE+
- 4 SFP/SFP+ slots for 10G Uplinks - compatible with S2x, S3x and S4x Series SFPs
- PD Alive Checking
- Up to 128Gbps non-blocking switch fabric
- MAC-based network access authentication
- Web based management
- 16K MAC address table
- VLAN Support - up to 256 VLANs groups
- Up to 370 Watt PoE Power Budget



# NS4702-24P-4X-V3

## Enterprise-class 24-port Gigabit backbone network switch with PoE+, 4-10G SFP+ uplinks

### Technical specifications

#### General

|                    |                               |
|--------------------|-------------------------------|
| Fast ring          | Yes (ERPS)                    |
| Storm control      | Broadcast, Multicast, Unicast |
| Fault relay output | No                            |

#### Category

|            |                        |
|------------|------------------------|
| Category   | Commercial, Enterprise |
| Management | Managed                |
| Managed    | Yes (Layer 2)          |
| PoE        | Yes                    |

#### Physical ports

|                |   |
|----------------|---|
| No. of ports   | 24  |
| Speed          | Gigabit   |
| PoE/PoE+       | IEEE 802.3at PoE+ on ports 1 to 24              |
| Fiber port     | 4 SFP/4 SFP+                                    |
| Supported SFPs | S20/S25 series, S30/S35 series, S40 series      |
| Console Port   | 1 x RJ45-to-RS232 serial port (115200, 8, N, 1) |

#### Switch performance

|                     |                       |
|---------------------|-----------------------|
| Switch fabric       | 128 Gbps/non-blocking |
| Throughput (Mpps)   | 95.23 Mpps            |
| Mac table           | 16 K                  |
| Jumbo frame support | 12 K                  |

#### Layer 2 Functions

|                        |  |
|------------------------|--|
| IGMP snooping          | 256 Group, Snooping v2, v3   |
| IGMP query             | Yes  |
| Port Mirroring         | TX/RX/both, Many-to-1 monitor, Up to 4 sessions  |
| VLAN                   | IEEE 802.1Q tagged VLAN, Up to 256 VLAN groups, out of 4094 VLAN IDs, IEEE 802.1ad Q-in-Q tunneling, Voice VLAN, Protocol VLAN, Private VLAN (Protected port), GVRP, Management VLAN   |
| Link Aggregation       | IEEE 802.3ad LACP and static trunk, Supports 8 groups with 8 ports per trunk   |
| Spanning Tree Protocol | IEEE 802.1D Spanning Tree Protocol (STP), IEEE 802.1w Rapid Spanning Tree Protocol (RSTP), IEEE 802.1s Multiple Spanning Tree Protocol (MSTP), Maximum 15 MSTP instances, STP BPDU Guard, BPDU Filtering and BPDU Forwarding |
| MLD Snooping           | MLD (v1/v2) snooping, up to 256 multicast groups   |
| QoS                    | 8 mapping IDs to 8 level priority queues: Port number, 802.1p priority, 802.1Q VLAN tag, DSCP field in IP packet, Traffic classification based, strict priority and WRR  |
| Ring                   | Supports ERPS, and complies with ITU-T G.8032. Recovery time < 450ms   |

#### Electrical

|                   |   |
|-------------------|---|
| PoE power budget  | 370 watts max   |
| Redundant power   | No  |
| Power supply type | 100 to 240 VAC  |
| Power consumption | 14.5 watts /49.4 BTU (System)<br>425 watts /1449 BTU (System+PoE) |

#### Physical

|                     |                              |
|---------------------|------------------------------|
| Physical dimensions | 440 x 207 x 44 mm, 1U Height |
| Net weight          | 3457 g                       |
| Colour              | Black                        |
| Material            | Metal                        |
| Mounting type       | 19" rack                     |
| Stackable           | No                           |

#### Environmental

|                       |                           |
|-----------------------|---------------------------|
| Operating temperature | 0 to 50°C                 |
| Storage temperature   | -20 to 70°C               |
| Relative humidity     | 5 to 95% (non-condensing) |
| Environment           | Indoor                    |

#### Power over Ethernet

|                       |                                       |
|-----------------------|---------------------------------------|
| PoE Standard          | IEEE 802.3af/at PoE+ PSE (Ports 1-24) |
| PoE Power Supply Type | End-span                              |
| PoE Power Output      | 32W (max)                             |
| Power Pin Assignment  | End-span: 1/2 (-), 3/6 (+)            |
| PoE Power Budget      | 370 watts (max.)                      |

#### PoE Management Functions

|                             |   |
|-----------------------------|---|
| Active PoE Device Detection | Yes   |
| PoE Power Recycle           | Yes, daily or predefined schedule                       |
| PoE Schedule                | 4 schedule profiles                                     |
| PoE Extend Mode             | Yes, max. up to 250 meters                              |
| PoE Port Management         | Port Enable/Disable/Schedule, Force mode, Port Priority |

#### Security Functions

|                     |   |
|---------------------|---|
| Access Control List | IPv4/IPv6 IP-based ACL/MAC-based ACL, IPv4/IPv6 IP-based ACE/MAC-based ACE, Max. 256 ACL entries  |
| Port Security       | IEEE 802.1X – Port-based authentication, Built-in RADIUS client to co-operate with RADIUS server, RADIUS/TACACS+ user access authentication |
| MAC Security        | IP-MAC port binding, MAC filter, Static MAC address, max. 256 static MAC entries  |
| Enhanced Security   | DHCP Snooping and DHCP Option82, STP BPDU guard, BPDU filtering and BPDU forwarding, DoS attack prevention, ARP inspection, IP source guard |



# NS4702-24P-4X-V3


## Enterprise-class 24-port Gigabit backbone network switch with PoE+, 4-10G SFP+ uplinks

### Management Functions

|                              |   |
|------------------------------|---|
| Basic Management Interfaces  | Web browser; Telnet; SNMP v1, v2c   |
| Secure Management Interfaces | SSHv2, TLS v1.2, SNMP v3  |
| System Management            | Firmware upgrade by HTTP/TFTP protocol through Ethernet network, LLDP protocol, SNTP, TruVision Device Manager discovery tool, TruVision Navigator VMS monitoring software.   |
| Event Management             | Remote Syslog, Local System log, Email SMTP   |
| SNMP MIBs                    | RFC 1213 MIB-II, RFC 1215 Generic Traps, RFC 1493 Bridge MIB, RFC 2674 Bridge MIB Extensions, RFC 2737 Entity MIB (v2), RFC 2819 RMON (1, 2, 3, 9), RFC 2863 Interface Group MIB, RFC 3635 Ethernet-like MIB, RFC 3621 Power Ethernet MIB |

### IEEE Standards

|                       |   |
|-----------------------|---|
| Standards Compliance  | IEEE 802.3 10BASE-T                             |
|                       | IEEE 802.3u 100BASE-TX/100BASE-FX               |
|                       | IEEE 802.3z Gigabit SX/LX                       |
|                       | IEEE 802.3ab Gigabit 1000T                      |
|                       | IEEE 802.3ae 10Gb/s Ethernet                    |
|                       | IEEE 802.3x flow control and back pressure      |
|                       | IEEE 802.3ad port trunk with LACP               |
|                       | IEEE 802.1D Spanning Tree Protocol              |
|                       | IEEE 802.1w Rapid Spanning Tree Protocol        |
|                       | IEEE 802.1s Multiple Spanning Tree Protocol     |
|                       | IEEE 802.1p Class of Service                    |
|                       | IEEE 802.1Q VLAN tagging                        |
|                       | IEEE 802.1x Port Authentication Network Control |
|                       | IEEE 802.1ab LLDP                               |
|                       | IEEE 802.3af Power over Ethernet                |
|                       | IEEE 802.3at Power over Ethernet Plus           |
|                       | IEEE 802.3az Energy Efficient Ethernet (EEE)    |
|                       | RFC 768 UDP                                     |
|                       | RFC 793 TFTP                                    |
|                       | RFC 791 IP                                      |
|                       | RFC 792 ICMP                                    |
|                       | RFC 2068 HTTP                                   |
|                       | RFC 1112 IGMP v1                                |
|                       | RFC 2236 IGMP v2                                |
|                       | RFC 3376 IGMP v3                                |
|                       | RFC 2710 MLD v1                                 |
|                       | RFC 3810 MLD v2                                 |
|                       | ITU G.8032 ERPS Ring                            |
| Regulatory compliance | UL, cUL   |



As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit [firesecurityproducts.com](https://firesecurityproducts.com) online or contact your sales representative.