

PB501

AIR Line Detector, 2 Lines, 20 m Outdoors, 40 m Indoors



Standard Features

- Range 20/40 metres
- Indoor and outdoor installation
- 2 Synchronised lines
- 4 Optional frequency steps ensure that one receiver will only 'see' one transmitter
- Adjustable precision optics
- Immune to external light
- High protection against EMC noise
- AGC sensitivity control
- Extra lens heater available as an accessory
- Full range of tower accessories for outdoor fitting

PB501

AIR Line Detector, 2 Lines, 20 m Outdoors, 40 m Indoors

Specifications

General	
Category	Active Infrared Beams
Product type	Active Infrared Beam
Infrared system	2-beam LED, double frequency modulation
Tamper	NC (max. charge 30 VAC/VDC - 100 mA)
Detection	
Range	20 / 40 m (outdoor / indoor)
Alarm response time	50 to 700 ms
Inputs/outputs	
Alarm output	NC/NO (max. charge 30 VAC/VDC - 0.5 mA)
Electrical	
Power supply value	12 to 30 VDC
Current consumption	55 mA
Physical	
Physical dimensions	72 x 170 x 70 mm
Net weight	380 g
Colour	Black
Material	Polycarbonate
Environmental	
Operating temperature	-25 to +60°C
Environment	Outdoor

Ordering Information

Part No.	Description
PB501	AIR Line Detector, 2 Lines, 20 m Outdoors, 40 m Indoors
PB103	Heating unit with thermostat for the PB 500 & 600 series, transmitter and receiver set
PB108	
PB109	
PB110	
PB112	
PB113	
PB114	