

# 4CH HD VIDEO + HIGH POWER PASSIVE BALUN

PTR-401VHP-HD



MODEL	PTR-401VHP-HD	
Input	4Ch BNC + 12-36VDC Power	
Output	4Ch BNC + 12VDC Power	
System Format	PAL / NTSC	
Input Resolution Support	5MP and Lower	
Input Signal Support	4 in 1 (AHD / CVI / TVI / CVBS)	
Transmission Distance	5MP	180m (AHD/TVI)
	4MP	180m (AHD/TVI)
	2MP	200m (AHD/TVI) / 230m (CVI)
	1MP	320m (AHD) / 250m (TVI) / 440m (CVI)
	960H and Lower	200m
Attenuation	1.5db Max	
Wiring	Cat5/5e/6 crimped cable (RJ-45)	
Surge Protection	2KV	
Work Environment	-20°C-70°C, 0%-90% Humidity	
Power Source	110/220VAC Power Input	
Dimensions	DVR Side - 300x260x67mm Camera Side - 73x29x20mm + 113mm Wire	
Net Weight	2.5Kg (DVR Side) + 60g (Camera Side)	

## Main Features:

- 4Ch Set
- 5MP 4in1 support: AHD / CVI / TVI / CVBS
- High-Power input - 12VDC Stable Output
- Plug and Play
- Passive
- Minimal Attenuation
- Light Weight Camera Side Unit

### Technology max. distance

Technology / Resolution	AHD	CVI	TVI
720P	320m	440m	250m
1080P	200m	230m	200m
4MP	180m		180m
5MP	180m		180m

### Power transmission max. distance

Power Supply / Power Consumption	DV 24V	DC 36V
200mA	400m	500m
300mA	350m	400m
400mA	300m	350m
500mA	240m	300m
600mA	190m	250m

