Eye-Sight

This series is designed for security professionals and offers superior image quality, advanced Al analytics, seamless connectivity, and unparalleled insight and protection, with options and configurations to meet specific needs. The Check Point Quantum IoT Nano and DDA2 Analytics provide detailed attribute analysis and advanced threat prevention.



TL-340IPERN-36

4MP DDA Analytics 24/7 Full-Color Fixed Lens Medium Bullet Camera

JE-SICI Rainbow series cameras are equipped with super light-sensitive sensors that allow the camera to provide a color image throughout the day. When the ambient light is insufficient, the camera will turn on the integral lighting, allowing it to continue providing a full-color image. The camera offers broad possibilities for Analytics, from Face Detection to the outstanding DDA Analytics (Detect, Distinguish, Alert), which can perform object recognition and object counting. With various detection rules and triggers, the TL-340IPERN-36 camera will help end false alarms. 3.6 mm 25m WDR Vhite I Fl rainbow DDA 1 ANALYTICS E LENS Οηνιέ **VNDAA** GG

MAIN FEATURES

- TL-340IPERN-36 4MP Rainbox Fixed Bullet Camera with White LED and DDA1 Analytics
- Sensor: 1/2.8" CMOS (16:9)
- Resolution: 2592×1520 25/30FPS (4MP)
- Lens: 3.6mm Fixed Lens (77.9°) 24/7 Full-Color Day Mode
- Illumination: 25m (2 High-Power White LED)
- Compression: H.265+/ H.264+ / H.265 / H.264 / MJPEG
- General Analytics: Camera Tampering

• Al (Object Recognition): DDA Sterile Area, DDA Line Crossing, DDA Object Counting

- Al (Face Detection): 10 Faces per frame
- True WDR (120dB), BLC, HLC, ROI
- SD Card: Event/Schedule Record (Up to 256Gb)
- Audio input
- ONVIF: Profile S/G
- Water Proof: IP67
- Weight: ~650g
- Power: DC12V/~780mA / PoE/~7.4W



https://provision-isr.com



SPECIFICATIONS

| 3rd Party Cyber Protection | | |
|----------------------------|---|--|
| General | N/A | |
| Protection Methods | N/A | |
| NDAA Compliant | | |
| NDAA Compliant | Yes | |
| Video | | |
| Image Sensor | 1/2.8" CMOS (16:9) | |
| Effective Pixels | 2592×1520 | |
| Electronic Shutter | 1/25s ~ 1/100000s | |
| Day & Night | 24/7 Full-Color Day Mode | |
| Min. Illumination | 0 lux (LED On) | |
| Audio | | |
| Audio compression | G.711A/G.711U | |
| Communication | One-Way Audio | |
| Image | | |
| Image Settings | AWB, AGC Adjustable, Exposure Mode (Auto) Sharpness, Saturation, Brightness & Contrast Adjustable | |
| Image Enhancement | True WDR (120dB), BLC, HLC, ROI | |
| Noise Reduction | 3D-DNR | |
| Image Orientation | Mirror/Flip, Corridor Mode | |
| Privacy Zone | Yes | |
| Events and Analytics | | |
| Analytics | General Analytics: Camera Tampering Al (Object Recognition): DDA Sterile Area, DDA Line Crossing, DDA Object Counting Al (Face Detection): 10 Faces per frame | |
| Motion Detection | Yes | |
| Compression | | |





| Resolution | 4MP/ 3MP / 2MP / 1MP / D1 / QVGA / CIF / QCIF | |
|----------------------|--|--|
| Frame Rate | 1-25/30FPS | |
| Video Compression | H.265+/ H.264+ / H.265 / H.264 / MJPEG** | |
| Multi-Stream | Master Stream: 4MP(2560x1440) / 3MP / 2MP / 1MP Substream: 1MP / D1 / CIF / QCIF Third Stream: D1 / CIF / QCIF (1~30fps) | |
| Bit Rate | 64Kbps ~ 7Mbps@H.265 / 64Kbps ~ 8Mbps@H.264 | |
| Encode Mode | VBR/CBR | |
| Image Quality | Five levels under VBR; Free adjustment under CBR | |
| Lens | | |
| Lens (Field of View) | 3.6mm Fixed Lens (77.9°) | |
| Iris | Fixed Iris | |
| Lens Mount | M12 Mount | |
| Network | | |
| User Access | Supports simultaneous monitoring of up to 10 users with multi-stream real- time transmission | |
| Network Protocol | IPv4, IPv6, TCP, UDP, DHCP, NTP, DDNS, 802.1X, RTSP, Multicast, UPnP, Email, FTP, HTTPS, QoS, P2P | |
| Remote Monitoring | IE Browsing (Plug-In required), Chrome/Edge/Safari/Firefox plug-in free browsing, Ossia VMS Software, Provision Cam2 Mobile App | |
| Ethernet | 100Mbps | |
| ONVIF | Profile S/G | |
| Connectivity | | |
| Network | RJ45 (+PoE) | |
| Audio Connectivity | Audio input | |
| Alarm | No | |
| SD Card | Event/Schedule based Main/Substream recording (Up to 256Gb) | |
| Wiegand | No | |

| Power | DC Socket |
|---------------------|------------------------------|
| Analog Video Output | No |
| Housing | |
| РоЕ | Yes |
| Illumination | 25m (2 High-Power White LED) |
| Power Supply | DC12V/~780mA / PoE/~7.4W |
| Protection Rate | Water Proof: IP67 |
| Work Environment | -30°C~60°C, 10%~90% Humidity |
| Bracket | 3-Axis Bracket |
| Dimensions | 220.8x79.4x81.2mm |
| Weight (gross) | ~650g |
| Hard Reset Button | Yes |



DIMENSIONS







ACCESSORIES

