



TTE GPRS Simple

GPRS Communication Module

Description


TTE GPRS Simple is a quad-band GPRS module for serial communication to Teletek Electronics Eclipse series panels. The module is used to send alarm messages to monitoring center or end-user. The module is mounted in small plastic box suitable for wall mounting.

TTE GPRS Simple can also be used for remote management, programming and monitoring of the security system together with Teletek Electronics panel and the AJAX SP PRO software application.

TTE GPRS Simple communication module is certified according the requirements of RED directive and EN60950-1.

Technical Specifications

- Power supply from the control panel
- Current Consumption:
 - Normal operation mode (Standby) 50 mA
 - Maximal consumption 150 mA
- Phone numbers for events notification 6
- Input filtration time 0.5 sec
- Input for AC monitoring 9-35 V AC
- Operating frequency 850/900/1800/1900 MHz
- Antenna connector (SMA) 50 Ohm
- Encryption AES 128 bits



CE1304

Functional Specifications

- SMS notifications for system events;
- LEDs for indication of the network status, trouble with the connection to the control panel, etc.;
- Remote access trough AJAX WEB and MobileTTE (iOS/Android) application;
- Connection with AJAX SP servers via IP or DNS address;
- Main IP and back-up IP for communication with AJAX SP PRO;
- SIA over IP reporting to AJAX SP;
- Micro USB port for module configuration;
- SIM interface;
- Optional 2GB micro SD card for voice messages - Voice Reporting and Voice Guiding (arming, disarming);
- Serial communication with ECLIPSE series control panels;
- Jumper for restoring of factory default settings.

Packing Information

- **Single packing box** - 1 unit TTE GPRS Simple (module), dimensions 105 x 108 x 46 mm
- **Master box** - 90 units TTE GPRS Simple, dimensions 560 x 362 x 320 mm

Compatible Product Range

- **Eclipse series** - Alarm control panels 8/ 16/ 32/ 99 zones
- **SB-U** - small universal box

Contact Information