



EN54-3 Type A
CERTIFIED
1328-CPR-0287



VALKYRIE CS

Conventional Wall Mount Sounder/ Beacon

The VALKYRIE CS is a wall mounted Conventional Sounder/ Beacon with low power consumption. Four different tones are available and selected using DIL switches 1 and 2.

Both continuous and pulsing outputs are provided via separate negative supply connections allowing for the presence of differentiated evacuation and alert sounds.

TECHNICAL SPECIFICATIONS		
SUPPLY VOLTAGE		20 V to 30 V DC
CURRENT - SOUNDER/ BEACON ACTIVE		10 mA - 280 mW @ 28 V DC
MAXIMUM SOUNDER OUTPUT		97 dB (@ 1 meter - 30 V DC)
MAX. CABLE SIZE		2.5 mm ²
OPERATING TEMPERATURE		-10°C to 55°C
MAX. HUMIDITY		95% RH Non-Condensing
COLOUR / CASE MATERIAL		Red or White / ABS and PC
PROTECTION CATEGORY		IP21C - Type A - Indoor use
DIMENSIONS		110 (D) x 85 (H) mm inc. base
WEIGHT		254 g - inc. mounting base
ORDER CODE		
VALKYRIE CS	1328-CPR-0287	CONVENTIONAL WALL SOUNDER
VALKYRIE CSB	1328-CPR-0287	CONVENTIONAL WALL SOUNDER/ BEACON