



VALKYRIE VOX A

ADDRESSABLE VOICE SOUNDER

The VALKYRIE VOX A is a wall mounted Addressable Voice Sounder which is available in either red or white housings. The VALKYRIE VOX A voice sounder is based on our successful Horn type sounder and sounder/ beacon. Up to 32 individually addressed sounders can be installed per loop occupying an address in the range 94 to 125, it can be also configured the shadow mode. The address is set using switches 1 to 5 of the 8 way DIL switch.

With message selection directly programmable via the standard sounder programming of GFE fire alarm control panels, the VALKYRIE VOX A, can broadcast up to 5 differentiated pre-loaded messages: Alert, Fire, Evacuation, Test and Silence Message. The desired messages can be downloaded from our own proprietary recording PC application (VOX LOADER), via a standard USB interface. This product is Loop Controlled and Loop Powered.

KEY FEATURES

- Multi-Message. Follows Panel's Sounder Programming
- Multi-Language
- 107 dBA maximum sounder output at 1 m
- Messages easily programmed via USB interface using dedicated software (VOX LOADER)
- Synchronization for fast activation.

TECHNICAL SPECIFICATIONS

SUPPLY VOLTAGE	Loop: 20V to 30V DC
LOOP CURRENT	0.7 mA (Quiescent) - 7.5 mA Max. (Sounder active or charging)
LOOP CURRENT - ALARM BEACON	1.4 mA
SOUNDER OUTPUT @ 1 METER	Tone 104 dBA - Voice Message 107 dBA
MAX. CABLE SIZE	2.5 mm ²
OPERATING TEMPERATURE	-10°C to 55°C
MAX. HUMIDITY	95% RH Non-Condensing
CASE MATERIAL	ABS and PC
COLOUR	Red or White
PROTECTION CATEGORY	IP21C - Type A - Indoor use
DIMENSIONS	110 (D) x 85.1 (A) mm
WEIGHT	270 g / 325 g - inc. mounting base

ORDER CODE**VALKYRIE VOX A**

ADDRESSABLE VOICE SOUNDER

VALKYRIE VOX AB

ADDRESSABLE VOICE SOUNDER WITH BEACON

